frequency range Max. amplifier power

| nominal impedance

Power consumption

S / N ratio

Input sensitivity

Input impedance

Inputs

2.5 W

Digital:

Analog: 1x unbal., stereo, RCA

interface, USB-A jack

2x digital optical input, TOSLINK, up to 96 kHz /

1x USB-B input for direct connection to PC (sound card function) 700 mV (3.5 mm TRS)

 $14 \text{ k}\Omega$ (3.5 mm TRS, RCA)

700 mV (RCA)

1x unbal., stereo, 3.5 mm

1x unbal., stereo, ELAC WL



	AIR-X BASE	AIR-X AMP		AIR-X 407	AIR-X 403
Height x Width x Depth	38 x 160 x 90 (98) mm	_	Height x Width x	1038 x 260 x 290 mm	308 x 166 x 270 mm
Weight	250 g	-	Depth		
Power supply voltage	5 V 0.5 A DC	115 to 240 V~	Weight	20.9 kg	7.8 kg
	(AC adaptor: 100 to 240 V~ 50 to 60 Hz)	50 to 60 Hz	Type	3-way, active, bass reflex	2-way, active, bass reflex
Mains fuse	_	T 3.15 A L 250 V (5 x 20 mm)	Woofer	2 x 150 mm, AS XR cone	1 x 150 mm, AS XR cone
			Tweeter	JET 5	JET 5
Wireless system specifications	Digital wireless audio link, 2.4 GHz, KleerNet by	Digital wireless audio link, 2.4 GHz, KleerNet by	Crossover frequency	450 2,550 Hz	2,700 Hz
•	SMSC - 4 simultaneous uncompressed stereo audio	SMSC - 4 simultaneous un- compressed stereo audio	Frequency range (IEC 268-5)	28 to 23,000 Hz	38 to 23,000 Hz
	streams 48 kHz 24 Bit	streams 48 kHz 24 Bit	Finish	Black, White High	Black, White High
Wireless system	70 m (free sight between	70 m (free sight between		Gloss	Gloss
operating range	AIR-X BASE and AIR-X speaker)	AIR-X BASE and AIR-X speaker)	Accessories in- cluded in delivery	magn. fixed fabric grille, M8 crossbars	magn. fixed fabric grille, silicone pads
Wireless RF frequency range	2,400 to 2,483.5 MHz	2,400 bis 2,483.5 MHz	,		
Wireless audio	10 to 23,000 Hz	10 to 23,000 Hz			

225 W | 4 Ω Class A/B

Appr. 100 dB (A) rel. to full

Digital wireless audio: 2.4 GHz KleerNet

1x balanced: XLR

700 mV (RCA)

7.8 kΩ (RCA) | 7.1 kΩ (XLR)


0 dBu (XLR)

1x unbalanced: RCA

320 W

Subject to errors and amendment.









- ▶ BS 403 AMP, Black High Gloss
- **▶** BS 403, fabric grille







Totally free but always connected. Incredible detail that doesn't compromise the overall musical performance. High-end sound with a serious fun factor.

Break free – stay connected: ELAC AIR-X



■ ★ I ■ ELAC Electroacustic GmbH

Rendsburger Landstraße 215 • 24113 Kiel • Germany
Phone +49-431-64774-0 • www.elac.com



AIR-X



Introducing a unique combination of wireless functionality and superlative sound quality.

One concept, one wish, one solution: The new AIR-X system, consisting of active loudspeakers fitted with the AIR-X AMP amplifier unit and the AIR-X BASE station, ushers in a new era of music reproduction. The technology makes its debut in the award-winning Line 400 loudspeakers. The AIR-X 403 and AIR-X 407 are a powerful expression of the new system's capabilities – offering outstanding precision and thrilling dynamics, with not a cable in sight.

This is wireless audio redefined to the highest standard, with ultra-precise DSP technology matched with classic analog amplification in the AIR-X AMP to deliver an unrivaled listening experience. Just add your favorite music to bring everything seamlessly together.

Break free – stay connected: ELAC AIR-X









- ▲ AIR-X BASE
- ▶ Stand LS 30, optional



Lossless and uncompressed signal trans- The BASE acts as the central control unit precise adjustments to the sound.

Multizone & Multisource

mission meets Class A/B amplification: the of the AIR-X system and can connect an AIR-X system is your quarantee of excepallmost unlimited number of AIR-X loudtional sound. The combined output of the speakers. It can transmit up to four signals AIR X AMP is 225 watts. Built-in DSP tech- to three different zones. With the option nology with 56-bit resolution allows for to connect up to three BASE stations in a system, the possibilities are endless.

AIR-X connections

not desired.

AIR-X 403

the right input on the AIR-X BASE is easy. systems, it proves beyond doubt the capa- expectations ... with ease. It is a passion-Analog inputs on the AIR-X AMP also allow bilities of a compact loudspeaker. Thanks ate performer that delights in revealing you to connect playback equipment in to the integrated AIR-X AMP, it delivers a every musical nuance. With huge dynamic situations where wireless transmission is powerful performance across the entire reserves on tap, it's also a perfect choice for frequency spectrum.

AIR-X 407

Whether analog or digital – finding Currently the smallest model in the AIR-X In any position, the AIR-X 407 exceeds larger rooms.

